

1-16. (CANCELED)

17. (CURRENTLY AMENDED) ~~[[The]]~~ An electrodynamic drive system (2) for a vehicle located between a drive source (4) and a transmission (16), having a single planetary gear set (12), which includes a sun gear (50), an internal gear (10), a planetary gear (36) and a planetary gear carrier (32), of which the planetary carrier (32) is connected to the transmission (16), the internal gear (10) is connected to the drive source (4) and the sun gear (50) is bound to at least one electric motor (22), with a shift clutch (40) located between the planetary gear carrier and the sun gear (50) and operable to bypass the planetary gear set (12), and a blocking device is provided for torque reinforcement during starting of the drive source (4) according to claim 14,

wherein the blocking device is a braking apparatus of the vehicle and a simultaneously engaged gear stage of the shift clutch (40).

C 18. (CURRENTLY AMENDED) ~~[[The]]~~ An electrodynamic drive system (2) for a vehicle located between a drive source (4) and a transmission (16), having a single planetary gear set (12), which includes a sun gear (50), an internal gear (10), a planetary gear (36) and a planetary gear carrier (32), of which the planetary carrier (32) is connected to the transmission (16), the internal gear (10) is connected to the drive source (4) and the sun gear (50) is bound to at least one electric motor (22), with a shift clutch (40) located between the planetary gear carrier and the sun gear (50) and operable to bypass the planetary gear set (12), and a blocking device is provided for torque reinforcement during starting of the drive source (4) according to claim 14,

wherein the blocking device is formed by an override clutch (59) on an input shaft (28) of the manual transmission (16).

19. (CANCELED).

20. (CANCELED).

21. (CURRENTLY AMENDED) ~~[[The]]~~ An electrodynamic drive system (2) for a vehicle located between a drive source (4) and a transmission (16), having a single planetary gear set (12), which includes a sun gear (50), an internal gear (10), a planetary gear (36) and a planetary gear carrier (32), of which the planetary carrier (32) is connected to the transmission (16), the internal gear (10) is connected to the drive source (4) and the sun gear (50) is bound to at least one electric motor (22), with a shift clutch (40) located between the planetary gear carrier and the sun gear (50) and operable to bypass the planetary gear set (12), according to claim 14,

wherein a plurality of electric motors (22) on the sun gear (50) act upon the planetary drive (12).

22. (CURRENTLY AMENDED) ~~[[The]]~~ An electrodynamic drive system (2) for a vehicle located between a drive source (4) and a transmission (16), having a single planetary gear set (12), which includes a sun gear (50), an internal gear (10), a planetary gear (36) and a planetary gear carrier (32), of which the planetary carrier (32) is connected to the transmission (16), the internal gear (10) is connected to the drive source (4) and the sun gear (50) is bound to at least one electric motor (22), with a shift clutch (40) located between the planetary gear carrier and the sun gear (50) and operable to bypass the planetary gear set (12), according to claim 14,

wherein the shift clutch (40) includes a dog clutch.

23. (CURRENTLY AMENDED) ~~[[The]]~~ An electrodynamic drive system (2) for a vehicle located between a drive source (4) and a transmission (16), having a single planetary gear set (12), which includes a sun gear (50), an internal gear (10), a planetary gear (36) and a planetary gear carrier (32), of which the planetary carrier (32) is connected to the transmission (16), the internal gear (10) is connected to the drive source (4) and the sun gear (50) is bound to at least one electric motor (22), with a shift clutch (40) located between the planetary gear carrier and the sun gear (50) and operable to bypass the planetary gear set (12), according to claim 14,

wherein a control is provided, which can regulate the at least one electric motor (22) in 4-quadrant operation.

24. (CURRENTLY AMENDED) An electrodynamic drive system (2) for a vehicle located between a drive source (4) and a transmission (16), having a single planetary gear set (12), which includes a sun gear (50), an internal gear (10), a planetary gear (36) and a planetary gear carrier (32), of which the planetary carrier (32) is connected to the ~~manual~~ transmission (16), the internal gear (10) is connected to the drive source (4) and the sun gear (50) is bound to at least one electric motor (22), with a shift clutch (40) located between the planetary gear carrier and the sun gear (50) and operable to bypass the planetary gear set (12);

a blocking device is provided for torque reinforcement during starting of the drive source (4); and

the blocking device is in the ~~manual~~ transmission (16) and is formed by the simultaneous engagement of two gear stages.

25. (CURRENTLY AMENDED) An electrodynamic drive system (2) for a vehicle located between a drive source (4) and a transmission (16), having a single planetary gear set (12), which includes a sun gear (50), an internal gear (10), a planetary gear (36) and a planetary gear carrier (32), of which the planetary carrier (32) is connected to the ~~manual~~ transmission (16), the internal gear (10) is connected to the drive source (4) and the sun gear (50) is bound to at least one electric motor (22), with a shift clutch (40) located between the planetary gear carrier and the sun gear (50) and operable to bypass the planetary gear set (12); and wherein between the drive source (4) and the electrodynamic drive system (2) an overrunning clutch (58) is provided.

C1 26. (PREVIOUSLY ADDED) The electrodynamic drive system (2) for a vehicle according to claim 25, wherein one of an eddy current brake and a hydrodynamic retarder (56) is placed on a shaft (42) of the planetary drive (12).

27. (PREVIOUSLY ADDED) The electrodynamic drive system (2) for a vehicle according to claim 25, wherein a plurality of electric motors (22) on the sun gear (50) act upon the planetary drive (12).

28. (PREVIOUSLY ADDED) The electrodynamic drive system (2) for a vehicle according to claim 25, wherein the shift clutch (40) includes a dog clutch.

29. (PREVIOUSLY ADDED) The electrodynamic drive system (2) for a vehicle according to claim 25, wherein a control is provided, which can regulate the at least one electric motor (22) in 4-quadrant operation.